

509.00 EUR

incl. 19% VAT, plus [shipping](#)



**Support:**  [Specifications](#)

|                                         |                                                                                                                                                                                                                                                                         |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chip                                    | Broadcom                                                                                                                                                                                                                                                                |
| Dimensions                              | 140x138x60mm                                                                                                                                                                                                                                                            |
| Certifications&Safety                   | CE, FCC, ROHS                                                                                                                                                                                                                                                           |
| I/O Ports                               | 8x 10/100/1000BaseT(X)<br>4x 1000 BaseSFP<br>RS-232(RJ45) Console port<br>LED: Power, port speed, port connection                                                                                                                                                       |
| Management                              | Support WEB Interface<br>IEEE802.3 10Base-T Ethernet standard<br>IEEE802.3u 100Base-TX/FX<br>IEEE802.3z 1000Base-X<br>IEEE802.3ab 1000Base-T(X)<br>IEEE802.3x Flow control<br>EEE802.1d STP<br>IEEE802.1w RSTP<br>IEEE802.1s MSTP<br>IEEE802.1p QoS<br>IEEE802.1ad QinQ |
| Standards                               | 10BASE-T: Category 3 and above non-mask / mask twisted pair (<=100 m)<br>100BASE-TX: Category 5 and above non-mask / mask twisted pair (<=100 m)<br>1000BASE-T: Category 5 and above non-mask / mask twisted pair (<=100 m)                                             |
| Network interface / Wire specifications |                                                                                                                                                                                                                                                                         |
| PoE Support                             | No                                                                                                                                                                                                                                                                      |
| Power input / consumption               | Input voltage 12-36VDC<br>Reverse connection protection<br>Power interface : 5pin terminal                                                                                                                                                                              |
| Operating temperature                   | -40~75°C                                                                                                                                                                                                                                                                |
| Cooling                                 | Fanless                                                                                                                                                                                                                                                                 |
| MTBF                                    | 100.000hrs                                                                                                                                                                                                                                                              |